

WIRELESS FIRE ALARM

FULL ADDRESSABLE & SECURITY

🌐 <https://www.artra.co.id/> ✉ info@artra.co.id



SMOKE HEAT DETECTOR CP90

- Addressable Device
- Support to Control Panel CP90
- Power Battery up to 1 Year
- Type battery 3,7VDC
- Firendly installation
- Temperature -10° ~ 50°C
- Humidity Max 90%
- Photoelectric Smoke Detector
- Heat Detector Temp. 56°C



GAS DETECTOR CP90

- Addressable Device
- Support to Control Panel CP90
- Power 220VAC
- Firendly installation
- Temperature -10° ~ 50°C
- Humidity Max 90%
- Gas leakage LPG detector
- LPG LEL 10% activation



MANUAL CALL POINT CP90

- Addressable Device
- Support to Control Panel CP90
- Power Battery up to 1 Year
- Type battery 3VDC
- Firendly installation
- Temperature -10° ~ 50°C
- Humidity Max 90%
- Manual Call Point
- Resettable with key



SOUNDER

- Sounder Konvensional
- Sound Up to 100dB
- Support to Control Panel CP90
- Firendly installation
- Temperature -10° ~ 50°C
- Humidity Max 90%



CONTROL PANEL CP90

- CPU Master based on 32bit Cortex-M3 core
- Utility touch screen
- Include backup battery
- Power supply 220VAC for charging
- Maximum 90 device addressable CP90
- Notification to all smartphone
- Temperature -10° ~ 50°C
- Humidity Max 90%



CAMERA FIRE CM90

- CPU Master based on 32bit Cortex-M3 core
- Utility touch screen
- Include backup battery
- Memory up to 30 days
- Power supply 220VAC for charging
- Maximum 90 device addressable CM90
- Notification to all smartphone
- Temperature -10° ~ 50°C



SOUNDER LAMP

- Sounder Konvensional
- Sound Up to 100dB
- Support to Control Panel CP90
- Firendly installation
- Temperature -10° ~ 50°C
- Humidity Max 90%